

MK2M2 Inertial Measurement Unit - Two-Pager Datasheet

1. Features

- Low-Drift Gyroscopes ($0.5^\circ/\text{hr}$)
- Low-Drift Accelerometers ($< 15 \mu\text{g}$)
- Interface: RS-422 or CAN-FD
- Power Usage: 1.2 W
- Voltage Range: +12 VDC to +34 VDC
- Body Dimensions: 40 x 40 x 25 mm
- Temperature Range: -40°C to $+85^\circ\text{C}$
- IP67 Rating



Figure 1: OSCP-MK2M2 Unit Illustration

2. Description

OSCP is developing a versatile family of MEMS-based Inertial Measurement Units (IMUs) featuring 11 degrees of freedom (DoF), including 3-axis MEMS Gyroscopes, 3-axis MEMS Accelerometers, 3-axis TMR Magnetometers and 2-axis MEMS Inclino-meters. The family's most compact form factor is designed for small drones, robotics, autonomous rail, and geospatial mapping applications. The gyroscopes design significantly improves fault tolerance and helps compensate for sensor drift over time, ensuring reliable and consistent angular rate measurements for precision navigation and control, even in demanding or harsh operating conditions.

3. Functional Block Diagram




Figure 2: OSCP-MK2M2 Functional Block Diagram

Distributed by:



4. Key Specifications

! Important Disclaimers

- Some specifications are still in a preliminary state and are subject to refinement.
- **All specifications are no longer guaranteed if the unit is opened.**

Parameter	Min.	Typical	Max.	Unit	Case Temperature T_c
x-axis, y-axis & z-axis MEMS Gyroscopes					
Dynamic Range (Selectable)	± 125	$\pm 250, \pm 500, \pm 1000$	$\pm 2000, \pm 4000$	$^{\circ}/\text{sec}$	
In-Run Bias Stability	0.5	< 1.0		$^{\circ}/\text{hr}$	$T_c = +25^{\circ}\text{C}$
Noise Density		0.001		$^{\circ}/\text{sec}/\sqrt{\text{Hz}}$	$T_c = +25^{\circ}\text{C}$
Angle Random Walk		0.06		$^{\circ}/\sqrt{\text{hr}}$	$T_c = +25^{\circ}\text{C}$
x-axis, y-axis & z-axis MEMS Accelerometers					
Dynamic Range (Selectable)	± 2	$\pm 4, \pm 8$	± 16	g	
In-Run Bias Stability		15		μg	$T_c = +25^{\circ}\text{C}$
Noise Density		15		$\mu g/\sqrt{\text{Hz}}$	$T_c = +25^{\circ}\text{C}$
Velocity Random Walk		0.008		$m/\text{sec}/\sqrt{\text{hr}}$	$T_c = +25^{\circ}\text{C}$
x-axis, y-axis & z-axis TMR Magnetometers					
Dynamic Range		± 20		G	
x-axis & y-axis MEMS Inclinometers					
Dynamic Range (Selectable)	± 0.5	$\pm 1.0, \pm 2.0$	± 3.0	g	$T_c = +25^{\circ}\text{C}$
Timings					
Power-On Time			500	ms	$T_c = +25^{\circ}\text{C}$
Output Data Rate	0	100	500	Hz	
Electrical & Mechanical					
Communication Protocol		RS-422 or CAN-FD			
Operating Voltage	12		34	V	$-40^{\circ}\text{C} \leq T_c \leq +70^{\circ}\text{C}$
Power Consumption		1.2		W	$-40^{\circ}\text{C} \leq T_c \leq +85^{\circ}\text{C}$
Operating Temperature	-40		+85	$^{\circ}\text{C}$	
Dimensions with Flanges			45 x 58.5 x 25	mm	
Weight		75		g	

5. Certifications & Environmental Testing

The MK2M2 has been validated by an independent ISO/IEC 17025 accredited laboratory.

Table 2: Certifications and Environmental Testing Results

Category	Result
Ingress Protection	
Rating	IP67 - IEC 60529:2019
Electromagnetic Compatibility	
Emissions	EN 55032 Class A, FCC Part 15, ICES-003
Immunity	EN 55035 / CISPR 35
Vibration & Shock	
Sine sweep	20 – 2000 Hz up to 8 g peak, all three axes
Shock	Half-sine up to 40 g peak, 11 ms, all three axes

Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Texim Europe B.V. its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Texim"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Texim makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product.


It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time.

All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts.

Please contact us if you have any questions about the contents of the datasheet.

This may not be the latest version of the datasheet. Please check with us if a later version is available.





Headquarters & Warehouse

Elektrostraat 17
NL-7483 PG Haaksbergen
The Netherlands

T: +31 (0)53 573 33 33
E: info@texim-europe.com
Homepage: www.texim-europe.com



The Netherlands

Elektrostraat 17
NL-7483 PG Haaksbergen

T: +31 (0)53 573 33 33
E: nl@texim-europe.com



Belgium

Zuiderlaan 14, box 10
B-1731 Zellik

T: +32 (0)2 462 01 00
E: belgium@texim-europe.com



UK & Ireland

St Mary's House, Church Lane
Carlton Le Moorland
Lincoln LN5 9HS

T: +44 (0)1522 789 555
E: uk@texim-europe.com



Germany

Bahnhofstrasse 92
D-25451 Quickborn

T: +49 (0)4106 627 07-0
E: germany@texim-europe.com



Germany

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: muenchen@texim-europe.com



Austria

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: austria@texim-europe.com



Nordic

Stockholmsgade 45
2100 Copenhagen

T: +45 88 20 26 30
E: nordic@texim-europe.com



Italy

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: italy@texim-europe.com