



**SPECIFICATION
FOR
LCM Module
KD035QVFMA064**

MODULE:	KD035QVFMA064
CUSTOMER:	

STARTEK	INITIAL	DATE
PREPARED BY		
CHECKED BY		
APPROVED BY		

CUSTOMER	INITIAL	DATE
APPROVED BY		

Distributed by:

www.texim-europe.com

Part. No	KD035QVFMA064	REV	V1.4	Page 1 of 31
----------	---------------	-----	------	--------------

常备库存
Stock For Sale

长期供货
Long Time supply

支持小量
NO MOQ

品种齐全
In Full Range

[illegible]

常备库存	长期供货	支持小量	品种齐全
Stock For Sale	Long Time supply	NO MOQ	In Full Range



Contents

* Description	4
1. Block Diagram	5
2. Outline dimension	6
3. Input terminal Pin Assignment	7
4. LCD Optical Characteristics	9
4.1 Optical specification	9
4.2 Measuring Condition	9
4.3 Measuring Equipment	10
5. Electrical Characteristics	12
5.1 Absolute Maximum Rating (Ta=25 VSS=0V)	12
5.2 DC Electrical Characteristics	12
5.3 LED Backlight Characteristics	13
6. AC Characteristic	15
6.1 Display Parallel 8-bit Interface Timing Characteristics (8080 system)	15
6.2 Display Parallel 16/18-bit Interface Timing Characteristics (8080 system)	16
6.3 Display Serial Interface Timing Characteristics (3-line SPI system)	17
6.4 Parallel RGB Interface Timing Characteristics	19
6.4.1 16 bit/pixel color order (R 5-bit, G 6-bit, B 5-bit), 65,536 colors (CSEL(2-0) = "101")	20
6.4.2 18 bit/pixel color order (R 6-bit, G 6-bit, B 6-bit), 262,144 colors (CSEL(2-0) = "110")	21
7. LCD Module Out-Going Quality Level	22
7.1 VISUAL & FUNCTION INSPECTION STANDARD	22
7.1.1 Inspection conditions	22
7.1.2 Definition	22
7.1.3 Sampling Plan	23
7.1.4 Criteria (Visual)	24
8. Reliability Test Result	29
9. Cautions and Handling Precautions	30
9.1 Handling and Operating the Module	30
9.2 Storage and Transportation	30
10. Packing	31

Part. No	KD035QVFMA064	REV	V1.4	Page 3 of 31
----------	---------------	-----	------	--------------

常备库存
Stock For Sale

长期供货
Long Time supply

支持小量
NO MOQ

品种齐全
In Full Range



* Description

This is a color active matrix TFT (Thin Film Transistor) LCD (liquid crystal display) that uses amorphous silicon TFT as a switching device. This model is composed of a Transmissive type TFT-LCD Panel, driver circuit, back-light unit. The resolution of a 3.5'TFT-LCD contains 240x320 pixels, and can display up to 65K/262K colors.

* Features

- Low Input Voltage: 3.3V(TYP)
- Display Colors of TFT LCD: 65K/262K colors
- Interface: 8/16/18Bit MCU Interface
 - 3 SPI+16/18Bit RGB Interface
 - 3 line Serial Interface

General Information Items	Specification	Unit	Note
	Main Panel		
Display area(AA)	53.28(H)*71.04 (V) (3.5inch)	mm	-
Driver element	TFT active matrix	-	-
Display colors	65K/262K	colors	-
Number of pixels	240(RGB)*320	dots	-
Pixel arrangement	RGB vertical stripe	-	-
Pixel pitch	0.222(H)*0.222(V)	mm	-
Viewing angle	Free	o'clock	-
Controller IC	HX8347A	-	-
Display mode	Transmissive/ Normally Black	-	-
Operating temperature	-30~+85	°C	-
Storage temperature	-40~+90	°C	-

* Mechanical Information

Item		Min.	Typ.	Max.	Unit	Note
Module size	Horizontal(H)		63.0		mm	-
	Vertical(V)		85.0		mm	-
	Depth(D)		3.0		mm	-
Weight			TBD		g	-

Part. No	KD035QVFMA064	REV	V1.4	Page 4 of 31
----------	---------------	-----	------	--------------


常备库存
Stock For Sale

长期供货
Long Time supply

支持小量
NO MOQ

品种齐全
In Full Range

1. Block Diagram



Part. No	KD035QVFMA064	REV	V1.4	Page 5 of 31
常备库存 Stock For Sale	长期供货 Long Time supply	支持小量 NO MOQ	品种齐全 In Full Range	



3. Input terminal Pin Assignment

NO.	SYMBOL	DISCRIPTION	I/O
1	GND	Ground.	P
2	XR (NC)	Touch panel Right Glass Terminal	A/D
3	YD(NC)	Touch panel Bottom Film Terminal	A/D
4	XL(NC)	Touch panel Left Glass Terminal	A/D
5	YU(NC)	Touch panel Top Film Terminal	A/D
6	BS0	MPU Parallel interface bus and serial interface select *If use RGB Interface must select serial interface. Fix this pin at VCI and GND.	I
7	BS1		I
8	BS2		I
9	NRESET	This signal will reset the device and must be applied to properly initialize the chip.	I
10	VSYN	Frame synchronizing signal for RGB interface operation. fix this pin at VCI or GND when not in use.	I
11	HSYN	Line synchronizing signal for RGB interface operation. fix this pin at VCI or GND when not in use	I
12	PCLK	Dot clock signal for RGB interface operation Fix this pin at VCI or GND when not in use.	I
13	DE	Data enable signal for RGB interface operation. fix this pin at VCI or GND when not in use.	I
14-31	DB17-DB0	18-bit parallel bi-directional data bus for MCU system and RGB interface mode . Fix to GND level when not in use	I
32	SDO	Serial data output pin in serial bus system interface. If not used, please open this pin.	O
33	SDI	Serial input signal.The data is applied on the rising edge of the SCL signal. If not used, fix this pin at VCI or GND.	I
34	NRD	Serves as a read signal and MCU read data at the rising edge. fix this pin at VCI or GND when not in use.	I
35	NWR	NWR pin, serves as a write signal	I
36	DNC_SCL	DNC_SCL pin as Serial Clock when operates in the serial interface	I

Part. No	KD035QVFMA064	REV	V1.4	Page 7 of 31
----------	---------------	-----	------	--------------

常备库存
Stock For Sale

长期供货
Long Time supply

支持小量
NO MOQ

品种齐全
In Full Range



37	NCS	Chip select input pin ("Low" enable). fix this pin at VCI or GND when not in use.	I
38	VCI	Supply voltage(3.3V).	P
39	VCI	Supply voltage(3.3V).	P
40	IOVCC	Supply voltage(1.8-3.3V)	P
41	LEDK1	Cathode pin OF backlight	P
42	LEDK2	Cathode pin OF backlight	P
43	LEDK3	Cathode pin OF backlight	P
44	LEDK4	Cathode pin OF backlight	P
45	LEDK5	Cathode pin OF backlight	P
46	LEDK6	Cathode pin OF backlight	P
47	LEDK7	Cathode pin OF backlight	P
48	LEDK8	Cathode pin OF backlight	P
49	LEDA	Anode pin of backlight	P
50	GND	Ground.	P

Part. No	KD035QVFMA064	REV	V1.4	Page 8 of 31
----------	---------------	-----	------	--------------

常备库存
Stock For Sale

长期供货
Long Time supply

支持小量
NO MOQ

品种齐全
In Full Range



4. LCD Optical Characteristics

4.1 Optical specification

Item		Symbol	Condition	Min.	Typ.	Max.	Unit.	Note
Contrast Ratio		CR	$\Theta=0$ Normal viewing angle	--	800	--	msec	
Response time	Rising	T _R		--	16	21		
	Falling	T _F		--	19	24		
Color gamut		S(%)		--	72	--	%	
Color Filter Chromaticity	White	W _X		0.336	0.340	0.344		
		W _Y		0.356	0.360	0.364		
	Red	R _X		0.618	0.620	0.622		
		R _Y		0.338	0.340	0.342		
	Green	G _X		0.348	0.350	0.352		
		G _Y		0.620	0.622	0.624		
	Blue	B _X		0.148	0.150	0.152		
		B _Y		0.033	0.035	0.037		
Viewing angle	Hor.	Θ_L	CR>10	--	80	--		
		Θ_R		--	80	--		
	Ver.	Θ_U		--	80	--		
		Θ_D		--	80	--		
		Option View Direction		Free				

4.2 Measuring Condition

- Measuring surrounding: dark room
- Ambient temperature: $25 \pm 2^\circ\text{C}$
- 15min. warm-up time.

Part. No	KD035QVFMA064	REV	V1.4	Page 9 of 31
----------	---------------	-----	------	--------------

常备库存
Stock For Sale


长期供货
Long Time supply

支持小量
NO MOQ

品种齐全
In Full Range


4.3 Measuring Equipment

- Note 1: Ambient temperature = 25°C.
- Note 2: To be measured with a viewing cone of 2° by Topcon luminance meter BM-5A.
- Note 3: To be measured with Otsuta chromaticity meter LCF-2100M, CF only measure under C light simulation.
- Note 4: CTC shipping status is cell without polarizer. Transmittance of Specification is cell with polarizer.
The tolerance of Transmittance is $\pm 10\%$.
- Note 5: Definition of response time:
The output signals of TRD-100 are measured when the input signals are changed to "White" (falling time) and from "White" to "Black" (rising time), respectively. The interval is between the 10% and 90% of amplitudes. Refer to figure as below.



- Note 6: Definition of contrast ratio:
Contrast ratio is calculated by the following formula.
- $$\text{Contrast ratio (CR)} = \frac{\text{Brightness on the "white" state}}{\text{Brightness on the "black" state}}$$


- Note 7: Definition of viewing angle




Part. No	KD035QVFMA064	REV	V1.4	Page 10 of 31
常备库存 Stock For Sale	长期供货 Long Time supply	支持小量 NO MOQ	品种齐全 In Full Range	



Note 8: Optical characteristic measurement setup.



Note 9:



$|LA - LA'| / LA \times 100\% = 2\% \text{ max.}$, LA and LA' are brightness at location A and A'.

$|LB - LB'| / LB \times 100\% = 2\% \text{ max.}$, LB and LB' are brightness at location B and B'.

Part. No	KD035QVFMA064	REV	V1.4	Page 11 of 31
----------	---------------	-----	------	---------------

常备库存
Stock For Sale

长期供货
Long Time supply

支持小量
NO MOQ

品种齐全
In Full Range



5. Electrical Characteristics

5.1 Absolute Maximum Rating (Ta=25 VSS=0V)

Characteristics	Symbol	Min.	Max.	Unit
Digital Supply Voltage	V _{CI}	-0.3	4.2	V
Digital interface supply Voltage	IOVCC	-0.3	3.3	V
Operating temperature	T _{OP}	-30	+85	°C
Storage temperature	T _{ST}	-40	+90	°C

NOTE:

If the absolute maximum rating of even is one of the above parameters is exceeded even momentarily, the quality of the product may be degraded. Absolute maximum ratings, therefore, specify the values exceeding which the product may be physically damaged. Be sure to use the product within the range of the absolute maximum ratings.

5.2 DC Electrical Characteristics

Characteristics	Symbol	Min.	Typ.	Max.	Unit	Note
Digital Supply Voltage	V _{CI}	2.5	2.8	3.3	V	
Digital interface supply Voltage	IOVCC	1.65	1.8	3.3	V	
Normal mode Current consumption	I _{DD}	--	9	--	mA	
Level input voltage	V _{IH}	0.7IOVCC		IOVCC	V	
	V _{IL}	GND		0.3IOVCC	V	
Level output voltage	V _{OH}	0.8IOVCC		IOVCC	V	
	V _{OL}	GND		0.2IOVCC	V	

Part. No	KD035QVFMA064	REV	V1.4	Page 12 of 31
----------	---------------	-----	------	---------------

常备库存
Stock For Sale

长期供货
Long Time supply

支持小量
NO MOQ

品种齐全
In Full Range



5.3 LED Backlight Characteristics

The back-light system is edge-lighting type with 8chips White LED

Item	Symbol	Min.	Typ.	Max.	Unit	Note
Forward Current	I_F	120	160	--	mA	
Forward Voltage	V_F	--	3.2	--	V	
LCM Luminance	L_v	400	450	--	cd/m ²	Note3
LED life time	Hr	50000	--	--	Hour	Note1,2
Uniformity	AVg	80	--	--	%	Note3


Note (1) :

LED life time (Hr) can be defined as the time in which it continues to operate under the condition:

$T_a = 25 \pm 3^\circ \text{C}$, typical IL value indicated in the above table until the brightness becomes less than 50%.

Note (2) The "LED life time" is defined as the module brightness decrease to 50% original brightness at

$T_a = 25^\circ \text{C}$ and $I_L = 160 \text{mA}$. The LED lifetime could be decreased if operating I_L is larger than 160mA. The constant current driving method is suggested.



LED(B/L) CIRCUIT

LED WHITE, 8 LED, 160mA, $3.2 \text{V} \pm 0.3 \text{V}$

Part. No	KD035QVFMA064	REV	V1.4	Page 13 of 31
----------	---------------	-----	------	---------------

常备库存
Stock For Sale


长期供货
Long Time supply

支持小量
NO MOQ

品种齐全
In Full Range



NOTE 3: Luminance Uniformity of these 9 points is defined as below:



Uniformity = $\frac{\text{minimum luminance in 9 points (1-9)}}{\text{maximum luminance in 9 points (1-9)}}$

Luminance = $\frac{\text{Total Luminance of 9 points}}{9}$

Part. No	KD035QVFMA064	REV	V1.4	Page 14 of 31
----------	---------------	-----	------	---------------


常备库存 Stock For Sale	长期供货 Long Time supply	支持小量 NO MOQ	品种齐全 In Full Range
------------------------	--------------------------	----------------	-----------------------




6. AC Characteristic

6.1 Display Parallel 8-bit Interface Timing Characteristics (8080 system)

Write to the register




Read the register






6.2 Display Parallel 16/18-bit Interface Timing Characteristics (8080 system)

Write to the graphic RAM (16-bit 65K Color / 18-bit bit 262K Color)




Read the graphic RAM (18-bit 262K Color)






6.3 Display Serial Interface Timing Characteristics (3-line SPI system)


A) Transfer Timing Format in Serial Bus Interface for Index Register or Register Write




B) Transfer Timing Format in Serial Bus Interface for GRAM write (index = "22h", TRI(1-0) = 00)



C) Transfer Timing Format in Serial Bus Interface for GRAM Write (index = "22h", TRI(1-0) = 01)



D) Transfer Timing Format in Serial Bus Interface for GRAM Write (index = "22h", TRI(1-0) = 1x)



Part. No	KD035QVFMA064	REV	V1.4	Page 17 of 31
----------	---------------	-----	------	---------------

常备库存
Stock For Sale


长期供货
Long Time supply

支持小量
NO MOQ


品种齐全
In Full Range




A) Transfer Timing Format in Serial Bus Interface for Register Read




B) Transfer Timing Format in Serial Bus Interface for GRAM Read (index = '22'h', TR[1:0] = 00)



C) Transfer Timing Format in Serial Bus Interface for GRAM Read (index = '22'h', TR[1:0] = 01)



D) Timing Format of GRAM -Data Read



Note: A RAM data read operation follows 8bit dummy read operations

Part. No	KD035QVFMA064	REV	V1.4	Page 18 of 31
----------	---------------	-----	------	---------------

常备库存
Stock For Sale

长期供货
Long Time supply

支持小量
NO MOQ

品种齐全
In Full Range



6.4 Parallel RGB Interface Timing Characteristics




Figure 5. 17 RGB Interface Circuit Input Timing

Part. No	KD035QVFMA064	REV	V1.4	Page 19 of 31
常备库存 Stock For Sale	长期供货 Long Time supply	支持小量 NO MOQ	品种齐全 In Full Range	



6.4.1 16 bit/pixel color order (R 5-bit, G 6-bit, B 5-bit), 65,536 colors (CSEL(2-0) = "101")




Figure 5. 18 16-Bit / Pixel Data Input of RGB Interface

Part. No	KD035QVFMA064	REV	V1.4	Page 20 of 31
----------	---------------	-----	------	---------------

常备库存
Stock For Sale


长期供货
Long Time supply

支持小量
NO MOQ

品种齐全
In Full Range



6.4.2 18 bit/pixel color order (R 6-bit, G 6-bit, B 6-bit), 262,144 colors (CSEL(2-0) = “110”)





7. LCD Module Out-Going Quality Level

7.1 VISUAL & FUNCTION INSPECTION STANDARD

7.1.1 Inspection conditions

Inspection performed under the following conditions is recommended.


Temperature : $25 \pm 5^{\circ}\text{C}$

Humidity : $65\% \pm 10\% \text{RH}$


Viewing Angle : Normal viewing Angle.

Illumination: Single fluorescent lamp (300 to 700Lux)

Viewing distance: 30-50cm



7.1.2 Definition



Zone A : Effective Viewing Area(Character or Digit can be seen)

Zone B : Viewing Area except Zone A

Zone C : Outside (Zone A+Zone B) which can not be seen after assembly by customer .)

Zone D : IC Bonding Area

Note:As a general rule ,visual defects in Zone C can be ignored when it doesn't effect product function or appearance after assembly by customer

Part. No	KD035QVFMA064	REV	V1.4	Page 22 of 31
常备库存 Stock For Sale		长期供货 Long Time supply		支持小量 NO MOQ
				品种齐全 In Full Range



7.1.3 Sampling Plan

According to GB/T 2828-2003 ; , normal inspection, Class II

AQL:




Major defect	Minor defect
0.65	1.5

LCD: Liquid Crystal Display , TP: Touch Panel , LCM: Liquid Crystal Module

No	Items to be inspected	Criteria	Classification of defects
1	Functional defects	1) No display, Open or miss line 2) Display abnormally, Short 3) Backlight no lighting, abnormal lighting. 4) TP no function	Major
2	Missing	Missing component	
3	Outline dimension	Overall outline dimension beyond the drawing is not allowed	
4	Color tone	Color unevenness, refer to limited sample	Minor
5	Spot Line defect	Light dot, Dim spot, Polarizer Bubble ; Polarizer accidented spot.	
6	Soldering appearance	Good soldering , Peeling off is not allowed.	
7	LCD/Polarizer/TP	Black/White spot/line, scratch, crack, etc.	



7.1.4 Criteria (Visual)

Number	Items	Criteria(mm)						
1.0 LCD Crack/Broken NOTE: X: Length Y: Width Z: Height L: Length of ITO, T: Height of LCD	(1) The edge of LCD broken	 <table><tr><td>X</td><td>Y</td><td>Z</td></tr><tr><td>≤3.0mm</td><td><Inner border line of the seal</td><td>≤T</td></tr></table>	X	Y	Z	≤3.0mm	<Inner border line of the seal	≤T
	X	Y	Z					
	≤3.0mm	<Inner border line of the seal	≤T					
(2)LCD corner broken	 <table><tr><td>X</td><td>Y</td><td>Z</td></tr><tr><td>≤3.0mm</td><td>≤L</td><td>≤T</td></tr></table>	X	Y	Z	≤3.0mm	≤L	≤T	
X	Y	Z						
≤3.0mm	≤L	≤T						
(3) LCD crack	 Crack Not allowed							

Part. No	KD035QVFMA064	REV	V1.4	Page 24 of 31
----------	---------------	-----	------	---------------

常备库存
Stock For Sale

长期供货
Long Time supply

支持小量
NO MOQ

品种齐全
In Full Range

X



3.0	Line defect (LCD/TP /Polarizer backlight black/white line, scratch, stain)	Width(mm)	Length(m m)	Acceptable Qty		
				A	B	C
		$\Phi\leq0.05$	Ignore	Ignore		Ignore
		$0.05<W\leq0.06$	$L\leq3.0$	$N\leq2$		
		$0.07<W\leq0.08$	$L\leq2.0$	$N\leq1$		
$0.08<W$	Define as spot defect					
4.0	Electronic Comp onents SMT	Not allow missing parts, solderless connection, cold solder joint, mis match, The positive and negative polarity opposite				
5.0	Display color& B rightness	1. Color: Measuring the color coordinates, The measurement standar d according to the datasheet or samples. 2. Brightness: Measuring the brightness of White screen, The measu rement standard according to the datasheet or Samples.				
6.0	LCD Mura	By 5% ND filter invisible.				

7.0	RTP Related	TP film • bubble/ accident spot					
			Size Φ (mm)	Acceptable Qty			
				A	B	C	
			$\Phi \leq 0.1$	Ignore			Ignore
			$0.1 < \Phi \leq 0.2$	3 (distance ≥ 10 mm)			
			$0.25 < \Phi \leq 0.3$	2			
$\Phi > 0.35$	0						

Part. No	KD035QVFMA064	REV	V1.4	Page 26 of 31
----------	---------------	-----	------	---------------

常备库存
Stock For Sale

长期供货
Long Time supply

支持小量
NO MOQ

品种齐全
In Full Range



			<table><tr><td rowspan="2">Width(mm)</td><td rowspan="2">Length(mm)</td><td colspan="3">Acceptable Qty</td></tr><tr><td>A</td><td>B</td><td>C</td></tr><tr><td>$\Phi\leq0.05$</td><td>Ignore</td><td colspan="2">Ignore</td><td rowspan="3">Ignore</td></tr><tr><td>$0.05<W\leq0.06$</td><td>$L\leq3.0$</td><td colspan="2">$N\leq2$</td></tr><tr><td>$0.07<W\leq0.08$</td><td>$L\leq2.0$</td><td colspan="2">$N\leq1$</td></tr><tr><td>$0.08<W$</td><td colspan="4">Define as spot defect</td></tr></table>	Width(mm)	Length(mm)	Acceptable Qty			A	B	C	$\Phi\leq0.05$	Ignore	Ignore		Ignore	$0.05<W\leq0.06$	$L\leq3.0$	$N\leq2$		$0.07<W\leq0.08$	$L\leq2.0$	$N\leq1$		$0.08<W$	Define as spot defect			
Width(mm)	Length(mm)	Acceptable Qty																											
		A	B	C																									
$\Phi\leq0.05$	Ignore	Ignore		Ignore																									
$0.05<W\leq0.06$	$L\leq3.0$	$N\leq2$																											
$0.07<W\leq0.08$	$L\leq2.0$	$N\leq1$																											
$0.08<W$	Define as spot defect																												
		Assembly deflection	beyond the edge of backlight $\leq0.2\text{mm}$																										
		Bulge (undulation included)	The ITO film plumped below 0.40mm, it's ok. 																										
		Newton Ring	<table><tr><td> Newton Ring area$>1/3$ TP area NG Newton Ring area$\leq1/3$ TP area OK </td><td> 1 规律性  2 非规律性  似牛顿环 </td></tr></table>	Newton Ring area$>1/3$ TP area NG Newton Ring area$\leq1/3$ TP area OK	 1 规律性  2 非规律性  似牛顿环																								
Newton Ring area$>1/3$ TP area NG Newton Ring area$\leq1/3$ TP area OK	 1 规律性  2 非规律性  似牛顿环																												

Part. No	KD035QVFMA064	REV	V1.4	Page 27 of 31
----------	---------------	-----	------	---------------



常备库存
Stock For Sale

长期供货
Long Time supply

支持小量
NO MOQ

品种齐全
In Full Range



		TP corner broken X : length Y : width Z : height	<table><tr><td>X</td><td>Y</td><td>Z</td></tr><tr><td>X≤3mm</td><td>Y≤3mm</td><td>Z<COVER thickness s</td></tr></table> *Circuitry broken is not allowed.	X	Y	Z	X≤3mm	Y≤3mm	Z<COVER thickness s	
X	Y	Z								
X≤3mm	Y≤3mm	Z<COVER thickness s								
		TP edge broken X : length Y : width Z : height	<table><tr><td>X</td><td>Y</td><td>Z</td></tr><tr><td>X≤4mm</td><td>Y≤2mm</td><td>Z<COVER thickness</td></tr></table> * Circuitry broken is not allowed.	X	Y	Z	X≤4mm	Y≤2mm	Z<COVER thickness	
X	Y	Z								
X≤4mm	Y≤2mm	Z<COVER thickness								

Criteria (functional items)

Number	Items	Criteria (mm)
1	No display	Not allowed
2	Missing segment	Not allowed
3	Short	Not allowed
4	Backlight no lighting	Not allowed
5	TP no function	Not allowed

Part. No	KD035QVFMA064	REV	V1.4	Page 28 of 31
----------	---------------	-----	------	---------------

常备库存
Stock For Sale

长期供货
Long Time supply

支持小量
NO MOQ

品种齐全
In Full Range



8. Reliability Test Result

Item	Condition	Inspection after test
High Temperature Operating	85℃, 96H	Inspection after 2~4hours storage at room temperature, the sample shall be free from defects: 1. Air bubble in the LCD; 2. Non-display; 3. Missing segments/line; 4. Glass crack; 5. Current IDD is twice higher than initial value.
Low Temperature Operating	-30℃, 96HR	
High Temperature Storage	90℃, 96HR	
Low Temperature Storage	-40℃, 96HR	
High Temperature & High Humidity Operating	+60℃, 90% RH, 96 hours.	
Thermal Shock (Non-operation)	-40℃, 30 min ↔ 90℃, 30 min, Change time: 5min 20CYC.	
ESD test	C=150pF, R=330, 5 points/panel Air: ±8KV, 5 times; Contact: ±6KV, 5 times; (Environment: 15℃~35℃, 30%~60%).	
Vibration (Non-operation)	Frequency range: 10~55Hz, Stroke: 1.5mm Sweep: 10Hz~55Hz~10Hz 2 hours for each direction of X.Y.Z. (6 hours for total) (Package condition).	
Box Drop Test	1 Corner 3 Edges 6 faces, 80cm (MEDIUM BOX)	

Remark:

1. The test samples should be applied to only one test item.
2. Sample size for each test item is 5~10pcs.
3. For Damp Proof Test, Pure water (Resistance > 10MΩ) should be used.
4. In case of malfunction defect caused by ESD damage, if it would be recovered to normal state after resetting, it would be judged as a good part.
5. Failure Judgment Criterion: Basic Specification, Electrical Characteristic, Mechanical Characteristic, Optical Characteristic.

Part. No	KD035QVFMA064	REV	V1.4	Page 29 of 31
----------	---------------	-----	------	---------------

常备库存
Stock For Sale

长期供货
Long Time supply

支持小量
NO MOQ

品种齐全
In Full Range



9. Cautions and Handling Precautions

9.1 Handling and Operating the Module

- (1) When the module is assembled, it should be attached to the system firmly.
Do not warp or twist the module during assembly work.
- (2) Protect the module from physical shock or any force. In addition to damage, this may cause improper operation or damage to the module and back-light unit.
- (3) Note that polarizer is very fragile and could be easily damaged. Do not press or scratch the surface.
- (4) Do not allow drops of water or chemicals to remain on the display surface.
If you have the droplets for a long time, staining and discoloration may occur.
- (5) If the surface of the polarizer is dirty, clean it using some absorbent cotton or soft cloth.
- (6) The desirable cleaners are water, IPA (Isopropyl Alcohol) or Hexane.
Do not use ketene type materials (ex. Acetone), Ethyl alcohol, Toluene, Ethyl acid or Methyl chloride. It might permanent damage to the polarizer due to chemical reaction.
- (7) If the liquid crystal material leaks from the panel, it should be kept away from the eyes or mouth. In case of contact with hands, legs, or clothes, it must be washed away thoroughly with soap.
- (8) Protect the module from static; it may cause damage to the CMOS ICs.
- (9) Use finger-stalls with soft gloves in order to keep display clean during the incoming inspection and assembly process.
- (10) Do not disassemble the module.
- (11) Protection film for polarizer on the module shall be slowly peeled off just before use so that the electrostatic charge can be minimized.
- (12) Pins of I/F connector shall not be touched directly with bare hands.
- (13) Do not connect, disconnect the module in the "Power ON" condition.
- (14) Power supply should always be turned on/off by the item 6.1 Power On Sequence & 6.2 Power Off Sequence

9.2 Storage and Transportation.

- (1) Do not leave the panel in high temperature, and high humidity for a long time.
It is highly recommended to store the module with temperature from 0 to 35 °C and relative humidity of less than 70%
- (2) Do not store the TFT-LCD module in direct sunlight.
- (3) The module shall be stored in a dark place. When storing the modules for a long time, be sure to adopt effective measures for protecting the modules from strong ultraviolet radiation, sunlight, or fluorescent light.
- (4) It is recommended that the modules should be stored under a condition where no condensation is allowed. Formation of dewdrops may cause an abnormal operation or a failure of the module.
In particular, the greatest possible care should be taken to prevent any module from being operated where condensation has occurred inside.
- (5) This panel has its circuitry FPC on the bottom side and should be handled carefully in order not to be stressed.

Part. No	KD035QVFMA064	REV	V1.4	Page 30 of 31
----------	---------------	-----	------	---------------

常备库存
Stock For Sale

长期供货
Long Time supply

支持小量
NO MOQ

品种齐全
In Full Range

10. Packing

---TBD-----

ISO9001 : 2008
ISO/TS16949 : 2009
TEXIM-EUROPE

Part. No	KD035QVFMA064	REV	V1.4	Page 31 of 31
常 备 库 存 Stock For Sale		长 期 供 货 Long Time supply		支 持 小 量 NO MOQ
				品 种 齐 全 In Full Range

Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Texim Europe B.V. its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Texim"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Texim makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product.


It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time.

All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts.

Please contact us if you have any questions about the contents of the datasheet.

This may not be the latest version of the datasheet. Please check with us if a later version is available.





Headquarters & Warehouse

Elektrostraat 17
NL-7483 PG Haaksbergen
The Netherlands

T: +31 (0)53 573 33 33
E: info@texim-europe.com
Homepage: www.texim-europe.com



The Netherlands

Elektrostraat 17
NL-7483 PG Haaksbergen

T: +31 (0)53 573 33 33
E: nl@texim-europe.com



Belgium

Zuiderlaan 14, box 10
B-1731 Zellik

T: +32 (0)2 462 01 00
E: belgium@texim-europe.com



UK & Ireland

St Mary's House, Church Lane
Carlton Le Moorland
Lincoln LN5 9HS

T: +44 (0)1522 789 555
E: uk@texim-europe.com



Germany

Bahnhofstrasse 92
D-25451 Quickborn

T: +49 (0)4106 627 07-0
E: germany@texim-europe.com



Germany

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: muenchen@texim-europe.com



Austria

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: austria@texim-europe.com



Nordic

Stockholmsgade 45
2100 Copenhagen

T: +45 88 20 26 30
E: nordic@texim-europe.com



Italy

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: italy@texim-europe.com