Distributed by www.texim-europe.com

Distributed by:
TEXIM EUROPE
www.texim-europe.com

TFT DISPLAY SPECIFICATION



WINSTAR Display Co.,Ltd.
華凌光電股份有限公司

Distributed by www.texim-europe.com

Winstar Display Co., LTD
華凌光電股份有限公司
WEB: https://www.winstar.com.tw E-mail: sales@winstar.com.tw

SPECIFICATION

CUSTOMER : _____

MODULE NO.: WFN0520A2S0YADNN000

APPROVED BY: **(FOR CUSTOMER USE ONLY)**	**PCB VERSION:** **DATA:** ☐ TFT Display Inspection Specification: https://www.winstar.com.tw/technology/download.html ☐ Precaution in use of TFT module: https://www.winstar.com.tw/technology/download/declaration.html

SALES BY	APPROVED BY	CHECKED BY	PREPARED BY
			葉虹蘭
ISSUED DATE:	**2026/07/23**		

Distributed by www.texim-europe.com

Winstar Display Co., LTD
華凌光電股份有限公司

MODLE NO：

RECORDS OF REVISION			DOC. FIRST ISSUE
VERSION	DATE	REVISED PAGE NO.	**SUMMARY**
0	2026/07/23		First issue

TEXIM EUROPE

Distributed by www.texim-europe.com

Contents

1.Module Classification Information

2.Summary

3.General Specifications

4.Absolute Maximum Ratings

5.Electrical Characteristics

6.Input Data Format

7.Power ON/OFF Sequence

8.Optical Characteristics

9.Interface

10.Block Diagram

11.Reliability

12.Contour Drawing

13.Display start address setting

14.Other

Distributed by www.texim-europe.com

1.Module Classification Information

W	F	N	0520	A2	S	0Y	A	D	N	N	0	00
①	②	③	④	⑤	⑥	⑦	⑧	⑨	⑩	⑪	⑫	⑬

①	Brand：WINSTAR DISPLAY CORPORATION
②	Display Type：F→TFT Type, J→Custom TFT
③	N: Normal　E：EFD　M：MIP
④	Display Size：5.2” TFT
⑤	Model serials no.

⑥ Backlight Type：

F：	CCFL, White	T：	LED, White
S：	LED, High Light White	Z：	Nichia LED, White
N：	With out Backlight	A：	Front Light

⑦ LCD Polarize Type/ Temperature range/ Gray Scale Inversion Direction

Operating Temperature	Normal temperature					Super Wide temperature					
LCD tape	TN			IPS	VA	TN				IPS	VA
View angle	6H	12H	3H			6H	12H	O-Film	OD-Film		
Reflective	AA	-	-	-	AT	AN	-	-	-	AW	AV
Transflective	0B	0E	BN	AC	02	0M	0P	-	-	08	04
Transmissive	0C	0F	-	0A	0T	0N	0Q	0R	0S	0W	0V

Operating Temperature	Wide temperature									
LCD tape	TN								IPS	VA
View angle	6H	12H	2H	3H	9H	O-Film	OD-Film	All View		
Reflective	AG	AJ	AB	-	AW	-	-	05	AY	AX
Transflective	0H	0K	-	0G	-	0U	-	-	07	03
Transmissive	0I	0L	-	-	0W	0Z	0J	-	0Y	0X

⑧

A：	TFT LCD	G：	TFT+ Screw holes
B：	TFT+ Screw holes+ Control board	H：	TFT+ D/V board
C：	TFT+ Screw holes + A/D board	I：	TFT+ Screw holes +D/V board
D：	TFT+ Screw holes + A/D board + Control board	J：	TFT+ Power board
E：	TFT+ Screw holes + Power board	Z：	TFT+ Power board (Embedded)
F：	TFT+ Control board		

⑨

A：Analog	B：6-bits parallel	D：Digital	E：eDP
L：LVDS	M：MIPI	S：SPI	

⑩ Interface:

A：8Bit	B：16Bit	E：eDP	H：HDMI	I：I2C Interface	L：LVDS
M：MIPI	N：Without Control board	P：DP	R：RS232	S：SPI	U：USB

⑪ TS:

A：	CTP + Optical bonding	B：	CTP + USB	C：	CTP
D：	CTP + USB + Optical bonding	E：	RTP + Optical bonding	F：	CG + Optical bonding
H：	CTP + Only G-sensor	J：	CTP + Only G-sensor + USB	L：	CTP+ Hover Touch
N：	Without TS	Q：	in-cell	R：	on-cell
T：	RTP	U：	CG	V：	in-cell + CG
W：	on-cell + CG				

⑫	Version:
⑬	Serial No.: Serial number (00~99)

Distributed by www.texim-europe.com

2.Summary

WFN0520A2S0YADNN000 is a color active matrix TFT LCD module using amorphous silicon TFT‘ s (Thin Film Transistors) as an active switching devices. It is a transmissive type display operating in the normal black. The TFT-LCD has a 5.2 inch diagonally measured active area with 480*128 resolutions .Each pixel is divided into RED, GREEN, BLUE dots which are arranged in vertical stripe and this panel can display 16.7M colors. The TFT-LCD panel used for this module is adapted for a low reflection and higher Luminance type.

Distributed by www.texim-europe.com

3.General Specifications

Item	Dimension	Unit
Size	5.2	inch
Dot Matrix	480 x RGB x 128	dots
Module dimension	140.4 x 49.87 x 3.0	mm
Active area	132.48 x 35.328	mm
Pixel pitch	0.276 x 0.276	mm
LCD type	TFT, Normally black, Transmissive	
View Angle	85/85/85/85	
Aspect Ratio	Bar Type	
Backlight Type	LED,Normally White	
TFT Driver IC	ILI6485D or Equal	
TFT Interface	RGB 24bit	
With /Without TP	Without TP	
Surface	Glare	

*Color tone slight changed by temperature and driving voltage.

Distributed by www.texim-europe.com

4.Absolute Maximum Ratings

Item	Symbol	Min	Typ	Max	Unit
Operating Temperature	TOP	-20	—	+70	℃
Storage Temperature	TST	-30	—	+80	℃

Note: Device is subject to be damaged permanently if stresses beyond those absolute maximum ratings listed above

1. Temp. ≦ 60℃, 90% RH MAX. Temp.＞60℃, Absolute humidity shall be less than 90% RH at 60℃

Distributed by www.texim-europe.com

5.Electrical Characteristics


5.1. Operating conditions:

Item	Symbol	Min	Typ	Max	Unit
Supply Voltage For LCM	VCC	3.0	3.3	3.6	V
Supply Current For LCM	ICC	—	17.0	26.0	mA

5.2. LED driving conditions

Parameter	Symbol	Min.	Typ.	Max.	Unit	Remark
LED current	—	—	80	—	mA	
LED voltage	VLED+	15.0	16.8	18.6	V	Note 1
LED Life Time	—	50,000	—	—	Hr	Note 2,3,4

Note 1 : There are 1 Groups LED



Note 2 : Ta = 25 ℃
Note 3 : Brightness to be decreased to 50% of the initial value
Note 4 : The single LED lamp case

Distributed by www.texim-europe.com

6.Input Data Format

6.1. RGB Input Timing Table

RGB input timing table (VCC= 3.3V, VSS= 0V, TA=25ºC).

1 Parallel 24-bit RGB Timing Table

Item		Symbol	Min.	Typ.	Max.	Unit	Remark
DCLK Frequency		Fclk	8	9	12	MHz	
DCLK Period		Tclk	125	111	83	ns	
HSYNC	Period Time	Th	485	531	598	DCLK	
	Display Period	Thdisp	-	480	-	DCLK	
	Back Porch	Thbp	3	43	43	DCLK	By H_Blanking setting
	Front Porch	Thfp	2	8	75	DCLK	
	Pulse Width	Thw	2	4	75	DCLK	
VSYNC	Period Time	Tv	276	292	321	H	
	Display Period	Tvdisp	-	272	-	H	
	Back Porch	Tvbp	2	12	12	H	By V_Blanking setting
	Front Porch	Tvfp	2	8	37	H	
	Pulse Width	Tvw	2	4	37	H	


Note:

1.It is necessary to keep Tvbp =12 and Thbp =43 in sync mode.

2.Thbp+Thfp >=5

Distributed by www.texim-europe.com


6.2. SYNC Mode Timing Diagram



Distributed by www.texim-europe.com

7.Power ON/OFF Sequence

7.1. Power On Sequence




Item	Description	Min. Time
T0	Determined by the external power.	
T1	Time from stable VDDI, VCI, VCIP set-up to the first frame.	T1=0
T2	Time from VSP_DC=0V to VSP_DC=3.3V.	T2=T0
T3	Time from VSP_DC =3.3V to VSP_DC =6.0V.	T3=T1+ (1*Frame)
T4	Time from stable VDDI, VCI, VCIP set-up to DISP asserted.	T4=0
T5	Time from VGH=0V to VGH=3.3V.	T5=T0

Note: Recommend the LCM power on rise time T0= 0~ 1ms

Distributed by www.texim-europe.com

7.2. Power Off Sequence



Item	Description	Min. Time
T0	Time from backlight power off to DISP=”L”.	1*Frame
T1	Time from DISP=”L” to LCM Power off.	5*Frame

Distributed by www.texim-europe.com

8.Optical Characteristics

Item		Symbol	Condition.	Min	Typ.	Max.	Unit	Remark
Response time		Tr+ Tf	θ=0°、Φ=0°	-	20	35	.ms	Note 3
Contrast ratio		CR	At optimized viewing angle	800	1000	-	-	Note 4
Color Chromaticity	White	Wx	θ=0°、Φ=0	0.26	0.31	0.36		Note 2,6,7
		Wy		0.299	0.349	0.399		
Viewing angle	Hor.	ΘR	CR≧10	80	85	-	Deg.	Note Note 1
		ΘL		80	85	-		
	Ver.	ΦT		80	85	-		
		ΦB		80	85	-		
Brightness		-	-	1000	1100	-	cd/m²	Center of display
Uniformity		(U)	-	75	-	-	%	Note5

Ta=25±2℃, IL=80mA

Note 1: Definition of viewing angle range




Fig. 8.1. Definition of viewing angle

Note 2: Test equipment setup:

After stabilizing and leaving the panel alone at a driven temperature for 10 minutes, the measurement should be executed. Measurement should be executed in a stable, windless, and dark room. Optical specifications are measured by Topcon BM-7or BM-5 luminance meter 1.0° field of view at a distance of 50cm and normal direction.





Fig. 8.2. Optical measurement system setup

Note 3: Definition of Response time:

The response time is defined as the LCD optical switching time interval between “White” state and “Black” state. Rise time, Tr, is the time between photo detector output intensity changed

Distributed by www.texim-europe.com

from 90%to 10%. And fall time, Tf, is the time between photo detector output intensity changed from 10%to 90%



Note 4: Definition of contrast ratio:
The contrast ratio is defined as the following expression.

$$\text{Contrast ratio (CR)} = \frac{\text{Luminance measured when LCD on the "White" state}}{\text{Luminance measured when LCD on the "Black" state}}$$

Note 5: Definition of Luminance Uniformity
Active area is divided into 9 measuring areas (reference the picture in below). Every measuring point is placed at the center of each measuring area.
Luminance Uniformity (U) = Lmin/Lmax x100%
L = Active area length
W = Active area width




Fig8.3. . Definition of uniformity

Note 6: Definition of color chromaticity (CIE 1931)
Color coordinates measured at the center point of LCD

Note 7: Measured at the center area of the panel when all the input terminals of LCD panel are electrically opened.

Distributed by www.texim-europe.com

9.Interface

9.1. LCM PIN Definition

Pin	Symbol	Function	Remark
1	VLED-	Power for LED backlight cathode	
2	VLED+	Power for LED backlight anode	
3	GND	Power ground	
4	VCC	Power voltage	
5	R0	Red data (LSB)	
6	R1	Red data	
7	R2	Red data	
8	R3	Red data	
9	R4	Red data	
10	R5	Red data	
11	R6	Red data	
12	R7	Red data (MSB)	
13	G0	Green data (LSB)	
14	G1	Green data	
15	G2	Green data	
16	G3	Green data	
17	G4	Green data	
18	G5	Green data	
19	G6	Green data	
20	G7	Green data (MSB)	
21	B0	Blue data (LSB)	
22	B1	Blue data	
23	B2	Blue data	
24	B3	Blue data	
25	B4	Blue data	
26	B5	Blue data	
27	B6	Blue data	
28	B7	Blue data (MSB)	
29	GND	Power ground	
30	CLK	Pixel clock (DCLK)	


Distributed by www.texim-europe.com

31	LR	Right /Left selection; Default R/L is Pull High	Note1,2
32	HSYNC	Horizontal sync signal; negative polarity	
33	VSYNC	Vertical sync signal; negative polarity	
34	NC	No connection	
35	UD	Up/down selection; Default U/D is Pull High	Note1,2
36	RESET	Reset signal	
37	NC	No connection	
38	NC	No connection	
39	NC	No connection	
40	NC	No connection	

Note 1: Selection of scanning mode, and LR,UD Pull High 10KΩ on FPC


Setting of scan control input		**Scanning direction**
UD	**LR**	
L	H	Down to up, left to right
H	L	Up to down, right to left
L	L	Down to up, right to left
H	H	Up to down, left to right

Note 2: Definition of scanning direction.Refer to the figure as below:



Distributed by www.texim-europe.com


10.Block Diagram



Distributed by www.texim-europe.com

11.Reliability


Content of Reliability Test (Wide temperature, -20℃~70℃)

Environmental Test			
Test Item	**Content of Test**	**Test Condition**	**Note**
High Temperature storage	Endurance test applying the high storage temperature for a long time.	80℃ 240hrs	2
Low Temperature storage	Endurance test applying the low storage temperature for a long time.	-30℃ 240hrs	1,2
High Temperature Operation	Endurance test applying the electric stress (Voltage & Current) and the thermal stress to the element for a long time.	70℃ 240hrs	2
Low Temperature Operation	Endurance test applying the electric stress under low temperature for a long time.	-20℃ 240hrs	1,2
High Temperature/ Humidity Operation	The module should be allowed to stand at 60℃,90%RH max	60℃,90%RH 240hrs	1,2
Thermal shock resistance	The sample should be allowed stand the following 10 cycles of storage -30℃ 25℃ 80℃  30min 5min 30min 1 cycle	-30℃/80℃ 10 cycles	2
Vibration test	Endurance test applying the vibration during transportation and using.	Total fixed amplitude : 1.5mm Vibration Frequency : 10~55Hz One cycle 60 seconds to 3 directions of X,Y,Z for Each 15 minutes	3
Static electricity test	Endurance test applying the electric stress to the terminal.	VS=TBDV(contact), TBDV(air), RS=330Ω CS=150pF 10 times	4

Note1: No dew condensation to be observed.
Note2: The function test shall be conducted after 4 hours storage at the normal Temperature and humidity after remove from the test chamber.
Note3: The packing have to including into the vibration testing.
Note4: Endurance test applying the electric stress to the finished product housing

Distributed by www.texim-europe.com

12.Contour Drawing




PIN NO.	SYMBOL	PIN NO.	SYMBOL
1	VLED-	21	B0
2	VLED+	22	B1
3	GND	23	B2
4	VCC	24	B3
5	R0	25	B4
6	R1	26	B5
7	R2	27	B6
8	R3	28	B7
9	R4	29	GND
10	R5	30	CLK
11	R6	31	LR
12	R7	32	Hsync
13	G0	33	Vsync
14	G1	34	NC
15	G2	35	UD
16	G3	36	RESET
17	G4	37	NC
18	G5	38	NC
19	G6	39	NC
20	G7	40	NC

The non-specified tolerance of dimension is ±0.3 mm .

Distributed by www.texim-europe.com

13.Display start address setting



Ex.

One horizontal line = 0x0213

VS period time = 0x0124

HS Blanking = 0x2b

VS Blanking = 0x10

HS Front Porch = 0x08

VS Front Porch = 0x08

Set Horizontal Flipped

Set Vertical Flipped

Suggestion：
Vertical Display Period
Start Position= 0x00

Insert 8 Vertical Line of Black data before Sending data

Note：
For different Controller ICs, the value of vertical display period start position need to be adjusted accordingly.

Distributed by www.texim-europe.com

winstar

LCM Sample Estimate Feedback Sheet

Module Number： _____

1、Panel Specification：

1.	Panel Type：	□ Pass	□ NG , _____
2.	View Direction：	□ Pass	□ NG , _____
3.	Numbers of Dots：	□ Pass	□ NG , _____
4.	View Area：	□ Pass	□ NG , _____
5.	Active Area：	□ Pass	□ NG , _____
6.	Operating Temperature：	□ Pass	□ NG , _____
7.	Storage Temperature：	□ Pass	□ NG , _____
8.	Others： _____		

2、Mechanical

1.	PCB Size：	□ Pass	□ NG , _____
2.	Frame Size：	□ Pass	□ NG , _____
3.	Material of Frame：	□ Pass	□ NG , _____
4.	Connector Position：	□ Pass	□ NG , _____
5.	Fix Hole Position：	□ Pass	□ NG , _____
6.	Backlight Position：	□ Pass	□ NG , _____
7.	Thickness of PCB：	□ Pass	□ NG , _____
8.	Height of Frame to PCB：	□ Pass	□ NG , _____
9.	Height of Module：	□ Pass	□ NG , _____
10.	Others：	□ Pass	□ NG , _____

3、Relative Hole Size：

1.	Pitch of Connector：	□ Pass	□ NG , _____
2.	Hole size of Connector：	□ Pass	□ NG , _____
3.	Mounting Hole size：	□ Pass	□ NG , _____
4.	Mounting Hole Type：	□ Pass	□ NG , _____
5.	Others：	□ Pass	□ NG , _____

4、Backlight Specification：

1.	B/L Type：	□ Pass	□ NG , _____
2.	B/L Color：	□ Pass	□ NG , _____
3.	B/L Driving Voltage (Reference for LED Type)：	□ Pass	□ NG , _____
4.	B/L Driving Current：	□ Pass	□ NG , _____
5.	Brightness of B/L：	□ Pass	□ NG , _____
6.	B/L Solder Method：	□ Pass	□ NG , _____
7.	Others：	□ Pass	□ NG , _____

>> **Go to page 2** <<

Distributed by www.texim-europe.com

5、**Electronic Characteristics of Module**：

1. Input Voltage： □ Pass □ NG ,_____
2. Supply Current： □ Pass □ NG ,_____
3. Driving Voltage for LCD： □ Pass □ NG ,_____
4. Contrast for LCD： □ Pass □ NG ,_____
5. B/L Driving Method： □ Pass □ NG ,_____
6. Negative Voltage Output： □ Pass □ NG ,_____
7. Interface Function： □ Pass □ NG ,_____
8. LCD Uniformity： □ Pass □ NG ,_____
9. ESD test： □ Pass □ NG ,_____
10. Others： □ Pass □ NG ,_____

6、**Summary**：

Sales signature：_____

Customer Signature：_____ **Date**：____/____/____

Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Texim Europe B.V. its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Texim”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Texim makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product.

It is the customer’s responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time.

All operating parameters, including typical parameters, must be validated for each customer application by the customer’s technical experts.

Please contact us if you have any questions about the contents of the datasheet.

This may not be the latest version of the datasheet. Please check with us if a later version is available.

Distributed by www.texim-europe.com

Texim Europe - contact details



Headquarters & Warehouse

Elektrostraat 17
NL-7483 PG Haaksbergen
The Netherlands

T: +31 (0)53 573 33 33
E: info@texim-europe.com
Homepage: www.texim-europe.com



The Netherlands

Elektrostraat 17
NL-7483 PG Haaksbergen

T: +31 (0)53 573 33 33
E: nl@texim-europe.com



Belgium

Zuiderlaan 14, box 10
B-1731 Zellik

T: +32 (0)2 462 01 00
E: belgium@texim-europe.com



UK & Ireland

St Mary's House, Church Lane
Carlton Le Moorland
Lincoln LN5 9HS

T: +44 (0)1522 789 555
E: uk@texim-europe.com



Germany

Bahnhofstrasse 92
D-25451 Quickborn

T: +49 (0)4106 627 07-0
E: germany@texim-europe.com



Germany

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: muenchen@texim-europe.com



Austria

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: austria@texim-europe.com



Nordic

Stockholmsgade 45
2100 Copenhagen

T: +45 88 20 26 30
E: nordic@texim-europe.com



Italy

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: italy@texim-europe.com