Distributed by:
TEXIM EUROPE
www.texim-europe.com

Easy Blade Baby 24

25.2 V | 17.4 Ah | 439 Wh | VKB: 56672 742 098

VARTA Storage GmbH - Rev No. 1 - 1225



*illustration only

ELECTRICAL SPECIFICATION

Power connection	Negative terminal: M6 (six) screw type, rated female terminal Positive terminal: M8 (eight) screw type, rated female terminal
CAN BUS connection	Type: 2x (two) M12-5, plug, female sockets, Mating style: screw thread Coding: A Model: TE part number T4111002051-000
Nominal voltage	25.2 V
Design capacity	17.4 Ah
Rated capacity	15.8 Ah
Design energy	439 Wh
Charging method	Constant Current + Constant Voltage
Max. charge voltage	29.05 V
Max. charge current	16 A (not for cycle life)
Rec. charge cut off	Current < 960 mA
Rec. discharge cut off	21 V
Max. continuous discharge current	49.5 A
Max. pulse discharge current	49.5 A for 3 sec.
Rec. charge current	8.25 A
Rec. discharge current	17.4 A
Exp. Cycle life at (0.5 C / 0.5 C), 22 °C ± 2 ° C	≥ 80 % of initial capacity at 1,200 cycles

GENERAL

(Battery with safety circuit and plastic/metal combination)

Size (l x w x h) [mm]	330 x 80 x 105
General	Lithium-Nickel-Manganese-Cobalt-Oxide with BMS
Communications	CAN BUS (CAN open)
Weight	Approx. 3.5 kg

CELL&BATTERY PROTECTION

Safety function	Short circuit protection: 300A /178µs Over discharge current protection 1: 49.5A / 3s; level 2: 57A / 50ms Over charge current protection 1: 18A / 3s; level 2 24A / 50ms
Fuse	100 A

ENVIROMENTAL CONDITIONS

Charge	0 °C to +45 °C
Discharge	-20 °C to +50 °C
Storage	1 to 3 months at -20 °C to +45 °C 1 year at -20 °C to +25 °C
Humidity	0 to 60 RH %
IP rating	IP 30, not water resistant

SAFETY CERTIFICATIONS

Please follow Handbook and VARTA handling & safety precautions for Lilon & LiPolymer. The cell used is a UL recognized component according to UL1642. This battery meets the requirements of battery directives and the battery parts are RoHS-compliant. This battery is certified according to UN38.3 and IEC62133-2:2017, UL2595, IEC60335.

FEATURES

- Easily connect up to 24 modules in parallel for higher capacities.
- Housing with locking feature for easy attachment to adjacent module.
- No external battery management needed.
- Automatic master-slave status established.
- Zero maintenance, zero emissions.
- Water sealed power connectors.
- Limited 2 year warranty.

The product is designed to safety standards per datasheet; the battery is NOT designed for intended use for e-mobility consumer products and road applications. Responsibility for system level safety remains with e-mobility product design to comply with safety standard for intended end markets.

Minimum order quantity: 240 pcs / Order multiples: 80 pcs
Product for OEM customers only. Distributor MOQs may vary.

Distributed by www.texim-europe.com

Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Texim Europe B.V. its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Texim”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Texim makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product.

It is the customer’s responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time.

All operating parameters, including typical parameters, must be validated for each customer application by the customer’s technical experts.

Please contact us if you have any questions about the contents of the datasheet.

This may not be the latest version of the datasheet. Please check with us if a later version is available.

Distributed by www.texim-europe.com

Texim Europe - contact details



Headquarters & Warehouse

Elektrostraat 17
NL-7483 PG Haaksbergen
The Netherlands

T: +31 (0)53 573 33 33
E: info@texim-europe.com
Homepage: www.texim-europe.com



The Netherlands

Elektrostraat 17
NL-7483 PG Haaksbergen

T: +31 (0)53 573 33 33
E: nl@texim-europe.com



Belgium

Zuiderlaan 14, box 10
B-1731 Zellik

T: +32 (0)2 462 01 00
E: belgium@texim-europe.com



UK & Ireland

St Mary's House, Church Lane
Carlton Le Moorland
Lincoln LN5 9HS

T: +44 (0)1522 789 555
E: uk@texim-europe.com



Germany

Bahnhofstrasse 92
D-25451 Quickborn

T: +49 (0)4106 627 07-0
E: germany@texim-europe.com



Germany

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: muenchen@texim-europe.com



Austria

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: austria@texim-europe.com



Nordic

Stockholmsgade 45
2100 Copenhagen

T: +45 88 20 26 30
E: nordic@texim-europe.com



Italy

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: italy@texim-europe.com