Distributed by www.texim-europe.com

TFT-LCD Module Specification

Module NO.: TST070WVBE-32C-V2

Version: V1.0

☐ APPROVAL FOR SPECIFICATION ☐ APPROVAL FOR SAMPLE

For Customer's Acceptance:	
Approved by	Comment
	Distributed by: TEXIM EUROPE www.texim-europe.com

TSD:		
Presented by	Reviewed by	Approved by
hcr	Aron	Aron

Revision history

Version No.	Date	Page	Content	Remark
V1.0	2025-8-20	All	The initial release	Aron

TEXIM EUROPE

CONTENTS

1 GENERAL CHARACTERISTICS ..... - 4 -

2 PRODUCT DRAWINGS ..... - 5 -

3 INTERFACE DESCRIPTION ..... - 6 -

3.1 LCM INTERFACE DESCRIPTION ..... - 6 -
3.2 CTP INTERFACE DESCRIPTION ..... - 7 -

4 RGB TIMING CHARACTERISTICS ..... - 7 -

5 ABSOLUTE MAXIMUM RATINGS ..... - 8 -

6 ELECTRICAL CHARACTERISTICS ..... - 8 -

7 BACKLIGHT CHARACTERISTICS ..... - 8 -

8 LCD OPTICAL SPECIFICATIONS ..... - 9 -

9 CAPACITIVE TOUCH PANEL SPECIFICATIONS ..... - 11 -

9.1 MECHANICAL CHARACTERISTICS ..... - 11 -
9.2 ELECTRICAL CHARACTERISTICS ..... - 11 -
9.3 INTERFACE TIMING CHARACTERISTICS ..... - 11 -

10 RELIABILITY TEST ..... - 12 -

11 SUGGESTIONS FOR USING LCD MODULES ..... - 13 -

11.1 HANDLING OF LCM ..... - 13 -
11.2 STORAGE ..... - 13 -

12 LIMITED WARRANTY ..... - 13 -

Distributed by www.texim-europe.com


1 General Characteristics

ITEM	Specification	Unit
LCD Type	a-Si TFT,Transmissive,Normally white,TN	-
LCD Size	7.0	inch
Resolution (W x H)	800× (RGB) × 480	pixel
CTP+LCM size	190.08(H)×121.92(V)×5.13(T)	mm
LCM size	164.9(H) × 100(V) × 3.25(T)	mm
Active Area	153.84 (H) × 85.63 V)	mm
Pixel Pitch	0.0641x3(H) × 0.1784(V)	mm
Viewing Direction	12 o'clock	-
Gray Scale Inversion Direction	6 o'clock	-
Color Depth	16.7M	-
Pixel Arrangement	RGB-stripe	-
Backlight Type	21 LEDs，60mA	-
Surface Luminance	400(Min),450(Typ)	cd/m²
Surface Treatment	Clear,hardness:6H	-
LCD Driver IC	EK9716BD/BD3&EK73002ACGB	-
Interface Type	LCD:TTL(RGB-24bit); CTP: I^2C	-
Input Voltage	3.3	V
With/Without TP	With CTP(ST1633i)	-
Weight	TBD	g

Note 1: RoHS compliant

Note 2: LCM weight tolerance: ± 5%.

2 Product drawings



PIN NAME	
1	LED-K
2	LED-A
3	GND
4	VDD
5	R0
6	R1
7	R2
8	R3
9	R4
10	R5
11	R6
12	R7
13	G0
14	G1
15	G2
16	G3
17	G4
18	G5
19	G6
20	G7
21	B0
22	B1
23	B2
24	B3
25	B4
26	B5
27	B6
28	B7
29	GND
30	DCLK
31	DISP
32	HSYNC
33	VSYNC
34	DEN
35	NC
36	GND
37	XR (NC)
38	YD (NC)
39	XL (NC)
40	YU (NC)

PIN NO	DEMARCATION
1	VDD
2	NC
3	RST
4	GND
5	INT
6	SDA (I2C_DAT)
7	SCL (I2C_CLK)
8	GND
9	GND
10	VDD (3.3V)

3 Interface description

3.1 LCM interface description


PIN NO.	Symbol	description
1	LED-K	Backlight K Cathode input pin.
2	LED-A	Backlight A Anode input pin.
3	GND	System Ground. (0V)
4	VDD	Power supply +3.3V
5~12	R0~R7	Red Data BUS
13~20	G0~G7	Green Data BUS
21~28	B0~B7	Blue Data BUS
29	GND	System Ground. (0V)
30	DCLK	Clock for input data. Data latched at rising/falling edge of this signal. Default is falling edge.
31	DISP	Standby mode control. (Normally pull high) DISP="L", enter standby mode for power saving. Timing controller and source driver will turn off, all outputs are Hi-Z. DISP="H", normal operation.
32	HSYNC	Horizontal sync input in digital parallel RGB. Negative polarity.
33	VSYNC	Vertical sync input in digital parallel RGB. Negative polarity.
34	DEN	Input data enable control. When DE mode, active High to enable data input. (Normally pull low)
35	NC	No connect
36	GND	System Ground. (0V)
37	XR/X+	No connect
38	YD/Y-	No connect
39	XL/X-	No connect
40	YU/Y+	No connect

3.2 CTP interface description


PIN NO.	Symbol	description
1	NC	No connect
2	NC	No connect
3	RST	External Reset, Low is active
4	GND	Ground. (0V)
5	INT	Interrupt request to the host
6	SDA	I2C data input and output
7	SCL	I2C clock input
8	GND	Ground. (0V)
9	GND	Ground. (0V)
10	VCC	Power supply +3.3V

4 RGB Timing Characteristics

Vertical input timing



Horizontal input timing



Parameter	Symbol	Value			Unit	Note
Horizontal	thd	800			DCLK	
DCLK frequency	fclk	Min.	Typ.	Max.	MHz	
		20	33.3	50		
1 Horizontal Line	th	908	928	1088	DCLK	thbp+thpw=88 DCLK is fixed.
HSD pulse width	thpw	-	48	-		
HSD back porch	thbp	40	40	40		
HSD front porth	thfp	20	40	200		
Parameter	Symbol	Value			Unit	Note

Parameter	Symbol	Min.	Typ.	Max.	Unit	Note
Vertical display area	tvd		480		H	
VSD period time	tv	513	525	711	H	tvpw+tvbp=32H is fixed
VSD pulse width	tvpw	1	1	3	H	
VSD Back Porch	tvbp	28	31	31	H	
VSD Front Porch	tvfp	5	14	200	H	
frame rate	fps	-	60	-	Hz	

5 Absolute Maximum Ratings

PARAMETER	SYMBOL	MIN	MAX	UNIT
Supply Voltage for Analog	VDD	-0.5	5.0	V
Operating Temperature	TOP	-20	70	° C
Storage Temperature	TST	-30	80	° C
Humidity	RH	-	90%(Max 60° C)	RH

6 Electrical Characteristics

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT
Analog operating voltage	VDD	3	3.3	3.6	V
Logic operating voltage	IOVDD	3	3.3	3.6	V
Input Current	IDD	-	TBD	-	mA
Input Voltage ' H ' level	VIH	0.7IOVCC	-	IOVCC	V
Input Voltage ' L ' level	VIL	GND	-	0.3IOVCC	

7 Backlight Characteristics

ITEM	SYMBOL	MIN	TYP	MAX	UNIT
Voltage for LED backlight	V_f	-	22.4	23	V
Current for LED backlight	I_f	-	60	-	mA
Power consumption	Wbl	-	1344	-	mW
Uniformity	Avg	75	80	-	%
LED Life Time	-	30000	40000	-	Hrs

Note:


1.The LED life time is defined as the module brightness decrease to 50% original brightness at Ta=25°C, 60%RH ±5 %.

2. The life time of LED will be reduced if LED is driven by high current, high ambient temperature and humidity conditions.
3. Typical operating life time is an estimated data.
4. Permanent damage to the device may occur if maximum values are exceeded or reverse voltage is loaded .Functional operation should be restricted to the conditions described under normal operating conditions.

8 LCD Optical specifications

Item	Symbol	Condition	Specification			Unit	Remark
			Min	Typ	Max		
Response time (By Quick)	Tr+Tf	θ = 0°	-	25	-	ms	Note 5
Contrast ratio	CR	θ = 0°	400	500	-		Note 2,6
Viewing angle	Top	CR≧10	70	75	-	Deg.	Note 2,6,7
	Bottom	CR≧10	65	70	-		
	Left	CR≧10	70	75	-		
	Right	CR≧10	70	75	-		
Color chromaticity （CIE1931）	Wx	θ = 0°	-0.02	0. 304	+0.02		Note 3
	Wy			0. 339			
	Rx			0. 601			
	Ry			0. 324			
	Gx			0. 301			
	Gy			0. 567			
	Bx			0. 143			
	By			0. 174			
NTSC			-	50%	-		Note 3


Note 1: Ambient temperature = 25°C.
Note 2: To be measured with a viewing cone of 2°by Topcon luminance meter BM-7
Note 3: To be measured with Otsuta chromaticity meter LCF-2100M, CF only measure under C light simulation.
Note 4: BOE shipping status is cell without polarizer. Transmittance of Specification is cell with polarizer. The tolerance of Transmittance is ±10%.
Note 5: Definition of response time:
The output signals of TRD-100 are measured when the input signals are changed to “White” (falling time) and from “White” to “Black” (rising time), respectively. The interval is between the 10% and 90% of amplitudes. Refer to figure as below.




Note 6: Definition of contrast ratio:
Contrast ratio is calculated by the following formula.

$$\text{Contrast ratio (CR)} = \frac{\text{Brightness on the "white" state}}{\text{Brightness on the "black" state}}$$


Note 7: Definition of viewing angle



Note 8: Optical characteristic measurement setup.



Note 9:



l LA-LA' l / LA x 100%= 2% max., LA and LA' are brightness at location A and A'.

l LB-LB' l / LB x 100%= 2% max., LB and LB' are brightness at location B and B'.

9 Capacitive Touch Panel specifications

9.1 Mechanical characteristics

DESCRIPTION	INL SPECIFICATION	REMARK
Touch Panel Size	7.0	
Outline Dimension (OD)	190.08(H) x 121.92(V) mm	Cover Lens Outline
Product Thickness	1.425mm	without gasket
Glass Thickness	0.7mm	
View Area	154.64x86.43mm	
Input Method	5 Fingers	
Activation Force	Touch	
Surface Hardness	≥6H	

9.2 Electrical characteristics

DESCRIPTION		SPECIFICATION
Operating Voltage		DC 2.8~3.3V
Power Consumption (IDD)	Active Mode	TBD
	Sleep Mode	TBD
Interface		I^2C
Controller IC		ST1633i
I^2C address		0x55
Resolution		800*480


9.3 Interface timing characteristics

PARAMETER	MIN	MAX	UNIT
SCL Frequency	-	400K	Hz
Bus Free Time Between a STOP and START Condition	1.3	-	uS
Hold Time (repeated) START Condition	0.6	-	uS
Data Setup Time	100	-	nS
Setup Time for Repeated START Condition	0.6	-	uS
Setup Time for STOP Condition	0.6	-	uS

10 RELIABILITY TEST

NO.	TEST ITEM	TEST CONDITION	INSPECTION AFTER TEST
1	High Temperature Storage	80±2°C/96 hours	Inspection after 2~4 hours storage at room temperature and humidity. The condensation is not accepted. The sample shall be free from defects: 1. Air bubble in the LCD 2. Seal leak 3. Non-display 4. Missing segments 5. Glass crack
2	Low Temperature Storage	-30±2°C/96 hours	
3	High Temperature Operating	70±2°C/96 hours	
4	Low Temperature Operating	-20±2°C/96 hours	
5	Temperature Cycle	-30±2°C ~ 25~ 80± 2°C × 10 cycles (30 min.) (5min.) (30min.)	
6	Damp Proof Test	60°C ±5°C × 90%RH/96 hours	
7	Vibration Test	Frequency 10Hz~55Hz Stroke: 1.5mm Sweep: 10Hz~150 Hz~10Hz 2 hours For each direction of X, Y, Z	
8	Shock Test	Half-sine, wave, 300m/s	
9	Packing Drop Test	Height: 60 cm 1 corner, concrete floor	
10	Electrostatic Discharge Test	C=150pF, R=330 Ω Air: ±8KV 150pF/330Ω 30 times Contact: ±4KV,20 times	
11	Image Sticking	25℃,60%RH (ref.to Remark(1))/30 minutes	

Remark (1): Switch the image to Grey 127 after displaying the 5*8 chess pattern for 30 minutes, the afterimage disappears within 10 seconds.



5*8 chess pattern　　Gray127

11 Suggestions for using LCD modules

11.1 Handling of LCM

1. The LCD screen is made of glass. Don't give excessive external shock, or drop from a high place.
2. If the LCD screen is damaged and the liquid crystal leaks out, do not lick and swallow. When the liquid is attach to your hand, skin, cloth etc, wash it off by using soap and water thoroughly and immediately.
3. Don't apply excessive force on the surface of the LCM.
4. If the surface is contaminated, clean it with soft cloth. If the LCM is severely contaminated, use Isopropyl alcohol/Ethyl alcohol to clean. Other solvents may damage the polarizer. The following solvents is especially prohibited: water , ketone Aromatic solvents etc.
5. Exercise care to minimize corrosion of the electrode. Corrosion of the electrodes is accelerated by water droplets, moisture condensation or a current flow in a high-humidity environment.
6. Install the LCD Module by using the mounting holes. When mounting the LCD module make sure it is free of twisting, warping and distortion. In particular, do not forcibly pull or bend the I/O cable or the backlight cable.
7. Don't disassemble the LCM.
8. To prevent destruction of the elements by static electricity, be careful to maintain an optimum work environment.
- Be sure to ground the body when handling the LCD modules.
- Tools required for assembling, such as soldering irons, must be properly grounded.
- To reduce the amount of static electricity generated, do not conduct assembling and other work under dry conditions.
- The LCD module is coated with a film to protect the display surface. Exercise care when peeling off this protective film since static electricity may be generated.

9. Do not alter, modify or change the the shape of the tab on the metal frame.
10. Do not make extra holes on the printed circuit board, modify its shape or change the positions of components to be attached.
11. Do not damage or modify the pattern writing on the printed circuit board.
12. Absolutely do not modify the zebra rubber strip (conductive rubber) or heat seal connector
13. Except for soldering the interface, do not make any alterations or modifications with a soldering iron.
14. Do not drop, bend or twist LCM.

11.2 Storage

1. Store in an ambient temperature of 5 to 45 C, and in a relative humidity of 40% to 60%. Don't expose to sunlight or fluorescent light.
2. Storage in a clean environment, free from dust, active gas, and solvent.
3. Store in antistatic container.

12 Limited Warranty

1.Our warranty liability is limited to repair and/or replacement. We will not be responsible for any consequential loss.

2.If possible, we suggest customer to use up all LCD modules as soon as possible. If the LCD module storage time over twelve months, we suggest to recheck it before being used.

3.Any product issues must be feedback to TSD within 12 months since delivery, otherwise, we will not be responsible for the subsequent or consequential events.

Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Texim Europe B.V. its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Texim”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Texim makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product.

It is the customer’s responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time.


All operating parameters, including typical parameters, must be validated for each customer application by the customer’s technical experts.

Please contact us if you have any questions about the contents of the datasheet.

This may not be the latest version of the datasheet. Please check with us if a later version is available.

Distributed by www.texim-europe.com

Texim Europe - contact details



Headquarters & Warehouse

Elektrostraat 17
NL-7483 PG Haaksbergen
The Netherlands

T: +31 (0)53 573 33 33
E: info@texim-europe.com
Homepage: www.texim-europe.com



The Netherlands

Elektrostraat 17
NL-7483 PG Haaksbergen

T: +31 (0)53 573 33 33
E: nl@texim-europe.com



Belgium

Zuiderlaan 14, box 10
B-1731 Zellik

T: +32 (0)2 462 01 00
E: belgium@texim-europe.com



UK & Ireland

St Mary's House, Church Lane
Carlton Le Moorland
Lincoln LN5 9HS

T: +44 (0)1522 789 555
E: uk@texim-europe.com



Germany

Bahnhofstrasse 92
D-25451 Quickborn

T: +49 (0)4106 627 07-0
E: germany@texim-europe.com



Germany

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: muenchen@texim-europe.com



Austria

Warwitzstrasse 9
A-5020 Salzburg

T: +43 (0)662 216 026
E: austria@texim-europe.com



Nordic

Stockholmsgade 45
2100 Copenhagen

T: +45 88 20 26 30
E: nordic@texim-europe.com



Italy

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: italy@texim-europe.com