Distributed by www.texim-europe.com

Giada

Distributed by:
TEXIM EUROPE
www.texim-europe.com

Giada F301

High-End Fanless Digital Signage Mini PC



Product Highlights:

- Fanless, completely silent and ultra-thin design
- Ultra HD digital video via DP+HDMI
- Powered by Intel® Core™ i3-5010U
- High-speed USB3.0 data transfer
- Highly reliable unattended technology



Product Specifications

Dimension	260 x 175 x 35mm
CPU	Intel® Core™ i3-5010U dual core / 4 threads, 2.10GHz, max. TDP 15W
Chipset	Integrated into CPU
Graphics	Intel HD Graphics 5500 1x DP 1x HDMI
Memory	1x SO-DIMM (Max DDR3L 8GB)
Storage	1x mSATA 1x SATA III
Audio	Realtek® High Definition Audio 1x Audio-Out & SPDIF (3.5mm) 1x Mic-In (3.5mm)
Ethernet	1x Intel I218 Gigabit Ethernet controller 1x RJ45 port
Wireless	Optional IEEE 802.11 b/g/n WIFI module
IR	Onboard IR module Optional IR remote controller

Expansion Ports	3x Mini-PCI Express® (2x full-length for mSATA III SSD and PCIE + USB2.0 (3G/ TV); 1x half-length for WIFI module)
Peripheral Interfaces	2x COM (1x front, 1x rear panel) 4x USB3.0 (1x front, 1x rear panel) 2x USB2.0 1x DP 1x HDMI 1x RJ45 (1000M) 1x DC-IN port 19V
OS Support	Windows® 7, 8.1 & Linux®(X86)
BIOS	AMI EFI BIOS
Cooling	Fanless heatsink
Operating Temperature	0℃ ~ +40℃ / 32℉ ~ 104℉

The product appearance, specifications and features are subject to change. Giada reserves the right of final interpretation for the content hereinabove.

Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Texim Europe B.V. its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Texim”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Texim makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product.

It is the customer’s responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time.

All operating parameters, including typical parameters, must be validated for each customer application by the customer’s technical experts.

Please contact us if you have any questions about the contents of the datasheet.

This may not be the latest version of the datasheet. Please check with us if a later version is available.

Distributed by www.texim-europe.com

Texim Europe - contact details



Headquarters & Warehouse

Elektrostraat 17
NL-7483 PG Haaksbergen
The Netherlands

T: +31 (0)53 573 33 33
E: info@texim-europe.com
Homepage: www.texim-europe.com



The Netherlands

Elektrostraat 17
NL-7483 PG Haaksbergen

T: +31 (0)53 573 33 33
E: nl@texim-europe.com



Belgium

Zuiderlaan 14, box 10
B-1731 Zellik

T: +32 (0)2 462 01 00
E: belgium@texim-europe.com



UK & Ireland

St Mary's House, Church Lane
Carlton Le Moorland
Lincoln LN5 9HS

T: +44 (0)1522 789 555
E: uk@texim-europe.com



Germany

Bahnhofstrasse 92
D-25451 Quickborn

T: +49 (0)4106 627 07-0
E: germany@texim-europe.com



Germany

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: muenchen@texim-europe.com



Austria

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: austria@texim-europe.com



Nordic

Stockholmsgade 45
2100 Copenhagen

T: +45 88 20 26 30
E: nordic@texim-europe.com



Italy

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: italy@texim-europe.com